



EC-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EC-type examination in accordance with the article 10 of the PPE Directive (89/686/EEC) and has been shown to satisfy the relevant provisions of the Directive.

Certificate N° 0075/487/162/08/17/1193 - EXT 02/08/17

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : India Ltd.
Kolkata
India

Distributor : VICSA STEELPRO COLOMBIA S.A.S
KILOMETRO 7 AUTOPISTA MEDELLIN - CELTA TRADE PARK LOTE
49 BODEGA 1 - FUNZA COLOMBIA

Description

PPE Type : protective glove against mechanical risks

Product reference : 300850680249

Glove description : Upper is flower leather, back cuff is undressed leather, elastic tightening at the back and blue fabric border at the end of the cuff

This product is a category II.

Available sizes : 6 7 8 9 10 11

Pictures :



Reference standard :

Levels of performance / class of protection

EN 420:2003+A1:2009

-

EN 388:2016

3 1 2 2 X

The levels of performance have been measured on the palm

« X » means that the test hasn't been performed ; no protection is required

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EC-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from August 2017

NOTA : Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with law n° R.4313-38 of the French Code of Work

Issued in Lyon by

Date of issue : August 18th, 2017

Lionel Gaudillere
PPE certification manager



www.ctcgroupe.com

cemarking@ctcgroupe.com



In application of the Directive 89/686/EEC of the 21th December 1989, concerning the alignment of member state legislation relating to personal protective equipment and in application of relevant requirements of the french labor code, providing by the transcription of these Directive into french regulation.

CTC - 4, rue de la République - 69367 Lyon cedex 07 - France
Tel : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cui Chaussure Maroquinerie Couture
Lui 78.654 du 22.09.1978 - Siret 77564972609160 - Code NAF 9412Z - TVA FR 81775649726

MANUFACTURER'S TECHNICAL FILE

Reference of the product : **300850680249**

Technical file index : **01**

Last update : **August 2017**

IDENTIFICATION

Reference of the product : 300850680249
Minor Variant 300850680019
Technical file index : 01
Last update : August 2017

Manufacturer :

India Ltd.
Kolkata
India

Factory :

India Ltd.
Kolkata
India

Distributor :

VICSA STEELPRO COLOMBIA S.A.S
CELTA TRADE PARK - LOTE 49
BODEGA 1 Funza Colombia
Tel : +57 8234090
Fax :

European Representative :

BUNZL PLC
York House, 45 Seymour Street, London
United Kingdom
tel : 07801 648484
fax :
web :
site : www.bunzl.com


GLOVE DESCRIPTION

Glove description :

Upper is flower leather, back cuff is undressed leather, elastic tightening at the back and blue fabric border at the end of the cuff

type of coating finish : no coating

Visual description :



Field of use, Risks against which the product protects :

Mechanical risk

Available sizes :

Minimum length of glove (mm)	Sizes
220	6
230	7
240	8
250	9
260	10
270	11

Glove constitution :

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		white	Buffalo Grain leather			0.9-1.1mm
Back		white	Buffalo Grain leather			0.9-1.1mm
		Natural	Buffalo Split leather			0.9-1.1mm
Cuff		white	Buffalo Grain leather			0.9-1.1mm
		White	Buffalo Split leather			0.9-1.1mm
		Natural	Elastic tape	132 g/sqm		
Binding		Blue	Cotton	160g/sqm		

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.
It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : Level 5
PH of glove and lining is greater than 3.5 and lower than 9.5 : yes
Chromium VI lower than the detection limit : conform
Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2016

Protection offered	Performance levels
Abrasion resistance	3
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm
« X » means that the test hasn't been performed ; no protection is required

TEST REPORTS

Laboratory	CTC	Other
EN 420	I170501453R I150300166	CH:TX:5420008956, CH:TX:6420006509, DELF15000681-REV2 14-03013
Azo	I170501453R	DELF15000681-REV2
EN 388	I170601758 I170501453R I170601587	CH:TX:5420008670
OTHER		DELF15000681-REV2

MARKING - PACKAGING

Information printed on the glove :

Logo of the authorized representative :

Logo 

Glove's reference : 300850680249

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Marking example :



Method of marking on the glove :

EC marking appears either by printing on the back of the glove or on a label sewn inside the glove

Packaging :

Each glove printed with logo, CE marking performance levels, 12 pairs packed in polybag

MEANS OF CONTROL

under ISO 9001

INSTRUCTION FOR USE

Mallcom India Ltd.

EN 12 Sector V, Salt Lake city, Kolkata 700091

India

Glove reference : 300850680249

Available sizes : 6 7 8 9 10 11

Glove description :

Upper is flower leather, back cuff is undressed leather, elastic tightening at the back and blue fabric border at the end of the cuff

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE : innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (OO75)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE


Applicable standards :

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : Level 5

Moreover, this glove has been designed for the following applications :

Application :

Mechanical hazard - EN 388



3 1 2 2 X

Levels of performance

Abrasion resistance	3	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

« X » means that the test hasn't been performed ; no protection is required

Protection limit :

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.