



REPORT

3933 US ROUTE 11 CORTLAND, NEW YORK 13045

Order No. G100766457

Revision Date: October 31, 2012
Original Issue Date: June 30, 2012

REPORT NO. 100766457CRT-001

TEST OF SAFETY GLASSES MODELS

| | |
|-----------|----------|
| SPY CLEAR | SPY GREY |
|-----------|----------|

RENDERED TO

VICSA SAFETY SA
PINTOR CICARELLI 683
8950002 SAN JOAQUIN, CHILE

REVISION NOTE: Changed NEAR UV from scientific notation to standard notation and two decimal places.

DATA REQUESTED

The client requested optical testing to Section 5 of ANSI Z87.1.

AUTHORIZATION

This test service was authorized by signed quote number 500380131.

REFERENCE DOCUMENTS:

The following Test Standards were used in part or in total to test each sample:

ANSI Z87.1 2010

American National Standard for Occupational and Educational
Personal Eye and Face Protection Devices

ASTM D1003 2007

Standard Test Method for Haze and Luminous Transmittance of
Transparent Plastics

DEVICES SUBMITTED

The samples were received by Intertek on June 21, 2012 in undamaged condition, and were tested as received. The sample designations were 250592-01 through 250592-02.

DATES OF TESTS

June 28, 2012 through June 29, 2012



EQUIPMENT LIST

| Equipment Used | Model Number | Control Number | Calibration Date | Calibration Due Date |
|-----------------------------|--------------|----------------|------------------|----------------------|
| Optronics Spectroradiometer | OL750D | E288 | 06/28/12 | 06/30/12 |
| Gardner Hazemeter | XL211 | N328 | 06/28/12 | 07/28/12 |
| Extech Hygrothermometer | 445703 | T1357 | 10/26/11 | 10/26/12 |
| Extech Hygrothermometer | 445703 | T1355 | 10/29/11 | 10/29/12 |
| Intertek 100ft Goniometer | NA | N060 | 08/12/11 | 08/12/12 |

TESTS

Section 5.1.1 Optical Quality:

Lenses shall be free of striae, bubbles, waves and other visible defects which would impair their optical quality.

Section 5.1.2 Luminous Transmission:

Clear lenses shall have a luminous transmission of not less than 85%. Clear and Filter lenses shall be labeled in accordance with Table 4a of ANSI Z87.1. Plano and prescription lenses shall comply with Tables 6 – 10 of ANSI Z87.1 where applicable.

Section 5.1.3 Haze:

Clear and plano lenses shall not exhibit more than 3% haze.

Section 5.1.4 Refractive Power, Astigmatism, Resolving Power, Prism and Prism Imbalance:

Lenses shall meet the tolerances for Refractive Power, Astigmatism and Resolving power as specified in Table 1 of ANSI Z87.1. Lenses shall meet the tolerances for Prism and Prism Imbalance as specified in Table 2 of ANSI Z87.1.

| Table 1: Tolerance on Refractive Power, Astigmatism and Resolving Power | | | |
|--|-------------------------|--------------------|------------------------|
| Protector | Refractive Power | Astigmatism | Resolving Power |
| Spectacle | ± 0.06 D | ≤ 0.06 D | Pattern 20 |
| Goggle | ± 0.06 D | ≤ 0.06 D | Pattern 20 |
| Faceshield Windows | No Requirement | No Requirement | Pattern 20 |
| Welding Helmet Lenses | ± 0.06 D | ≤ 0.06 D | Pattern 20 |

| Table 2: Tolerance on Prism and Prism Imbalance | | | | |
|--|----------------------|---------------------------|--------------------------|---------------------------|
| Protector | Prism | Vertical Imbalance | Base In Imbalance | Base Out Imbalance |
| Spectacle | ≤ 0.50 Δ | ≤ 0.25 Δ | ≤ 0.25 Δ | ≤ 0.50 Δ |
| Goggle | ≤ 0.25 Δ | ≤ 0.125 Δ | ≤ 0.125 Δ | ≤ 0.50 Δ |
| Faceshields | ≤ 0.37 Δ | ≤ 0.37 Δ | ≤ 0.125 Δ | ≤ 0.75 Δ |
| Welding Lenses | ≤ 0.50 Δ | ≤ 0.25 Δ | ≤ 0.25 Δ | ≤ 0.75 Δ |



RESULTS OF TEST

Section 5.1.1 Optical Quality:

| Control Number | Model Number | Defects | Notes | Pass/Fail |
|----------------|--------------|---------|-------|-----------|
| 250592 | Clear | None | --- | Pass |
| 250592 | Grey | None | --- | Pass |

Section 5.1.2 Luminous Transmission:

| Control Number | Model Number | Percent Transmittance | | Pass/Fail/NA |
|----------------|--------------|-----------------------|-----------|--------------|
| | | Left Eye | Right Eye | |
| 250592 | Clear | 91.6 | 91.6 | Pass |
| 250592 | Grey | 9.93 | 10.5 | NA |

Section 5.1.3 Haze:

| Control Number | Model Number | Percent Haze | | Pass/Fail/NA |
|----------------|--------------|--------------|-----------|--------------|
| | | Left Eye | Right Eye | |
| 250592 | Clear | 0.68 | 0.68 | Pass |
| 250592 | Grey | 0.52 | 0.40 | Pass |

Section 5.1.4 Refractive Power, Astigmatism, Resolving Power

| Control Number | Model Number | Eye | Refractive Power (diopeters) | Astigmatism (diopeters) | Resolving Power | Pass/Fail |
|----------------|--------------|-------|------------------------------|-------------------------|-----------------|-----------|
| 250592 | Clear | Left | 0.03 | 0.04 | 48 | Pass |
| | | Right | 0.03 | 0.04 | 48 | |
| 250592 | Grey | Left | 0.03 | 0.05 | 48 | Pass |
| | | Right | 0.02 | 0.05 | 48 | |

Section 5.1.4 Prism and Prism Imbalance

| Control Number | Model Number | Eye | Prism (Δ) | Vertical Imbalance (Δ) | Base in Imbalance (Δ) | Base Out Imbalance (Δ) | Pass/Fail |
|----------------|--------------|-------|--------------------|---------------------------------|--------------------------------|---------------------------------|-----------|
| 250592 | Clear | Left | 0.18 | 0.06 | 0.00 | 0.00 | Pass |
| | | Right | 0.23 | | | | |
| 250592 | Grey | Left | 0.18 | 0.00 | --- | 0.06 | Pass |
| | | Right | 0.14 | | | | |

Transmittance Ratings

| Control Number | Model Number | Eye | Visible Light Transmittance | L-Scale | UV Transmittance (%) | | |
|----------------|--------------|-------|-----------------------------|---------|----------------------|---------|---------|
| | | | (%) | | Far UV | Near UV | U-Scale |
| 250592 | Clear | Left | 91.6 | Clear | 0.00 | 0.00 | U6 |
| | | Right | 91.6 | | | | |
| 250592 | Grey | Left | 9.93 | L3 | 0.00 | 0.00 | U6 |
| | | Right | 10.5 | | | | |



PHOTO OF SAMPLE(S):

SPY CLEAR



SPY GREY



In Charge Of Tests:

Handwritten signature of Denis Niggli in black ink.

Denis Niggli
Engineer
Lighting Division

Report Reviewed By:

Handwritten signature of David Ellis in black ink.

David Ellis
Senior Project Engineer
Lighting Division

Attachment: None